

1  
2 10F 4 X A method of training door breach operations  
3 comprising the steps of:

4       Selecting a door breach training system comprising:

5           a door frame;

6           a door member hingedly attached to said door  
7           frame;

8           a door socket receptacle opening to an outer  
9           perimeter of said door member;

10          a door frame socket receptacle positioned in said  
11          door frame positioned for opposing said door  
12          socket receptacle in a coaxial orientation;

13          a door socket member with a door socket pin  
14          receptacle formed therein;

15          a door frame socket member with a door frame  
16          socket pin receptacle formed therein; and

17          a replaceable pin member sized and shaped for  
18          simultaneously extending, at opposite ends of  
19          said pin member, into both said door frame  
20          socket pin receptacle and said door socket  
21          pin receptacle, while spanning a space  
22          between said door member and said door frame;

Claims are renumbered.  
-10F

1 placing said door member in a closed position relative  
2 to said door frame;

3 positioning a first said replaceable pin member in a  
4 pre-exercise position wherein said pin member  
5 extends into both said door frame socket pin  
6 receptacle and said door socket pin receptacle,  
7 spanning said space between said door member and  
8 said door frame;

9 impacting said door with force sufficient to shear said  
10 replaceable pin member and open said door member;

11 replacing said first replaceable pin member with a  
12 second said replaceable pin member in said pre-  
13 exercise position; and

14 repeating said impacting step.

15  
16 105 4.5 The method of Claim 3 further comprising the step,  
17 before said positioning of said first replaceable pin  
18 member, of selecting said first replaceable pin member from  
19 alternative specification variant replaceable pin members,  
20 such variant specifications representing differing force  
21 required to shear said replaceable pin member.  
22  
23